



Déclaration de Performance

00055_4FCSUSP800ASF_2013/07/01	
1. Produit :	Foyer de cheminée à porte escamotable
2. Type / Version : [Article 11-4]	4 FACES SUSPENDU 800 AVEC SOLE FOYERE
3. Usage:	Foyer ouvert et inserts à alimentation manuelle pour combustibles minéraux solides
4. Nom et adresse du Fabricant: [Article 11-5]	TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39
5. Email	Commercial@totemfire.com
6. AVCP : Système d'évaluation et de vérification de la constance de la performance, Annexe V	Système 3
7. Organisme vérificateur agréé:	CTIF NB 1677 44 Av. De la division Leclerc F- 92318 Sèvres Cedex
Rapport de test:	TD 4020
8. Performances déclarées:	
Norme harmonisée	EN13229:2001/A2:2004/AC:2007
Caractéristiques essentielles	Performances
Sécurité incendie	
Réaction au feu	A1
Distance minimale aux matériaux combustibles	Distances minimales en mm Devant = 800 Dessus = 800 Sol = 0 Ce foyer est destiné à être habillé avec des épaisseurs d'isolants conformes aux exigences locales et aux instructions d'installation.
Risque d'incendie par la chute de combustible ardent	Satisfait

Emissions de combustion	CO [0.19%] Particules [_mg/m3]
Température de surface	Satisfait
Sécurité électrique	-
Possibilités d'entretien	Satisfait
Pression d'eau maximale de service	-
Température des fumées à la puissance nominale	T[212°C]
Résistance mécanique de support de la cheminée	NPD
Puissance thermique	
Puissance nominale	20 kW
Plage de puissance	-kW
Puissance de chauffage de l'eau	-*kW
Rendement	η [78%]

DECLARATION:

Les performances du produit identifié par les points 1 et 2 sont en conformité avec les performances déclarées au point 8.

Ces déclarations de performances sont sous la seule responsabilité du fabricant identifié par le point 4.

Signé pour le compte du fabricant par:

Alain Castagnol

Président TOTEM FIRE S.A.S

(Nom et fonction)

Malissard

01/07/2013

(Signature)




Declaration of Performance (DoP)

00055_4FCSUSP800ASF_2013/07/01															
1.	<table border="1"> <tr> <td>Product type :</td> <td>Inset appliance</td> </tr> </table>	Product type :	Inset appliance												
Product type :	Inset appliance														
2.	<table border="1"> <tr> <td>Type, Batch or serial number : [Article 11-4]</td> <td>4 FACES SUSPENDU 800 AVEC SOLE FOYERE</td> </tr> </table>	Type, Batch or serial number : [Article 11-4]	4 FACES SUSPENDU 800 AVEC SOLE FOYERE												
Type, Batch or serial number : [Article 11-4]	4 FACES SUSPENDU 800 AVEC SOLE FOYERE														
3.	<table border="1"> <tr> <td>Intended use of the product:</td> <td>Inset appliance without hot water supply</td> </tr> </table>	Intended use of the product:	Inset appliance without hot water supply												
Intended use of the product:	Inset appliance without hot water supply														
4.	<table border="1"> <tr> <td>Name and Address of the manufacturer: [Article 11-5]</td> <td>TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39</td> </tr> </table>	Name and Address of the manufacturer: [Article 11-5]	TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39												
Name and Address of the manufacturer: [Article 11-5]	TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39														
5.	<table border="1"> <tr> <td>Contact address: [Article 12-2]</td> <td>Commercial@totemfire.com</td> </tr> </table>	Contact address: [Article 12-2]	Commercial@totemfire.com												
Contact address: [Article 12-2]	Commercial@totemfire.com														
6.	<table border="1"> <tr> <td>AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V</td> <td>System 3</td> </tr> </table>	AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 3												
AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 3														
7.	<table border="1"> <tr> <td>Notified Body:</td> <td>CTIF NB 1677 44 Av. De la division Leclerc F- 92318 Sèvres Cedex</td> </tr> <tr> <td>Test Report no:</td> <td>TD 4020</td> </tr> </table>	Notified Body:	CTIF NB 1677 44 Av. De la division Leclerc F- 92318 Sèvres Cedex	Test Report no:	TD 4020										
Notified Body:	CTIF NB 1677 44 Av. De la division Leclerc F- 92318 Sèvres Cedex														
Test Report no:	TD 4020														
8.	<table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table>	Declared performance:		Harmonized technical specification	EN13229:2001/A2:2004/AC:2007	Essential characteristics	Performance	Fire safety		Reaction to fire	A1	Distance to combustible materials	Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.	Risk of burning fuel falling out	No
Declared performance:															
Harmonized technical specification	EN13229:2001/A2:2004/AC:2007														
Essential characteristics	Performance														
Fire safety															
Reaction to fire	A1														
Distance to combustible materials	Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.														
Risk of burning fuel falling out	No														

Emission of combustion products	CO [0.19%] PM [_mg/m3]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T[212°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	20 kW
Room heating output	-kW
Water heating output	-*kW
Energy efficiency	η [78%]

DECLARATION:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer by:

Alain Castagnol

Président TOTEM FIRE S.A.S

(Name and function)

Malissard 2013/07/01

(Place and date issue)

(Signature)
