

Déclaration de Performance

00064_4FCSUSP700TECH_2017/07/18	
1. Produit :	Foyer de cheminée à porte escamotable
2. Type / Version : [Article 11-4]	4 FACES SUSPENDU 700 TECHNIKA
3. Usage:	Foyer ouvert et inserts à alimentation manuelle pour combustibles minéraux solides
4. Nom et adresse du Fabricant: [Article 11-5]	TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39
5. Email	Commercial@totemfire.com
6. AVCP : Système d'évaluation et de vérification de la constance de la performance, Annexe V	Système 3
7. Organisme vérificateur agréé:	ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK
Rapport de test:	N°2013/0020
8. Performances déclarées:	
Norme harmonisée	EN13229:2001/A2:2004/AC:2007
Caractéristiques essentielles	Performances
Sécurité incendie	
Réaction au feu	A1
Distance minimale aux matériaux combustibles	Distances minimales en mm Devant = 800 Dessus = 800 Sol = 0 Ce foyer est destiné à être habillé avec des épaisseurs d'isolants conformes aux exigences locales et aux instructions d'installation.
Risque d'incendie par la chute de combustible ardent	Satisfait

Emissions de combustion	CO [0.18%] Particules [80mg/m3]
Température de surface	Satisfait
Sécurité électrique	-
Possibilités d'entretien	Satisfait
Pression d'eau maximale de service	-
Température des fumées à la puissance nominale	T[173°C]
Résistance mécanique de support de la cheminée	NPD
Puissance thermique	
Puissance nominale	16.9 kW
Plage de puissance	-kW
Puissance de chauffage de l'eau	-*kW
Rendement	η [79%]

DECLARATION:

Les performances du produit identifié par les points 1 et 2 sont en conformité avec les performances déclarées au point 8.

Ces déclarations de performances sont sous la seule responsabilité du fabricant identifié par le point 4.

Signé pour le compte du fabricant par:

Alain Castagnol

Président TOTEM FIRE S.A.S

(Nom et fonction)

Malissard

18/07/2017

(Signature)

Declaration of Performance (DoP)

00064_4FCSUSP800TECH_2018/07/18																																					
1.	<table border="1"> <tr> <td>Product type :</td> <td>Inset appliance</td> </tr> <tr> <td>Type, Batch or serial number : [Article 11-4]</td> <td>4 FACES SUSPENDU 700 TECHNIKA</td> </tr> <tr> <td>Intended use of the product:</td> <td>Inset appliance without hot water supply</td> </tr> <tr> <td>Name and Address of the manufacturer: [Article 11-5]</td> <td>TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39</td> </tr> <tr> <td>Contact address: [Article 12-2]</td> <td>Commercial@totemfire.com</td> </tr> <tr> <td>6.</td> <td> <table border="1"> <tr> <td>AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V</td> <td>System 3</td> </tr> <tr> <td>7.</td> <td> <table border="1"> <tr> <td>Notified Body:</td> <td>ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK</td> </tr> <tr> <td>Test Report no:</td> <td>N°2013/0020</td> </tr> </table> </td> </tr> <tr> <td>8.</td> <td> <table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table> </td> </tr> </table> </td></tr></table>	Product type :	Inset appliance	Type, Batch or serial number : [Article 11-4]	4 FACES SUSPENDU 700 TECHNIKA	Intended use of the product:	Inset appliance without hot water supply	Name and Address of the manufacturer: [Article 11-5]	TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39	Contact address: [Article 12-2]	Commercial@totemfire.com	6.	<table border="1"> <tr> <td>AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V</td> <td>System 3</td> </tr> <tr> <td>7.</td> <td> <table border="1"> <tr> <td>Notified Body:</td> <td>ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK</td> </tr> <tr> <td>Test Report no:</td> <td>N°2013/0020</td> </tr> </table> </td> </tr> <tr> <td>8.</td> <td> <table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table> </td> </tr> </table>	AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 3	7.	<table border="1"> <tr> <td>Notified Body:</td> <td>ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK</td> </tr> <tr> <td>Test Report no:</td> <td>N°2013/0020</td> </tr> </table>	Notified Body:	ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK	Test Report no:	N°2013/0020	8.	<table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table>	Declared performance:		Harmonized technical specification	EN13229:2001/A2:2004/AC:2007	Essential characteristics	Performance	Fire safety		Reaction to fire	A1	Distance to combustible materials	Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.	Risk of burning fuel falling out	No
Product type :	Inset appliance																																				
Type, Batch or serial number : [Article 11-4]	4 FACES SUSPENDU 700 TECHNIKA																																				
Intended use of the product:	Inset appliance without hot water supply																																				
Name and Address of the manufacturer: [Article 11-5]	TOTEM FIRE S.A.S 4 Avenue du Guimand F-26120 MALISSARD Tél : +33 (0)4 75 40 18 89 Fax : +33 (0)4 75 41 08 39																																				
Contact address: [Article 12-2]	Commercial@totemfire.com																																				
6.	<table border="1"> <tr> <td>AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V</td> <td>System 3</td> </tr> <tr> <td>7.</td> <td> <table border="1"> <tr> <td>Notified Body:</td> <td>ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK</td> </tr> <tr> <td>Test Report no:</td> <td>N°2013/0020</td> </tr> </table> </td> </tr> <tr> <td>8.</td> <td> <table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table> </td> </tr> </table>	AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 3	7.	<table border="1"> <tr> <td>Notified Body:</td> <td>ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK</td> </tr> <tr> <td>Test Report no:</td> <td>N°2013/0020</td> </tr> </table>	Notified Body:	ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK	Test Report no:	N°2013/0020	8.	<table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table>	Declared performance:		Harmonized technical specification	EN13229:2001/A2:2004/AC:2007	Essential characteristics	Performance	Fire safety		Reaction to fire	A1	Distance to combustible materials	Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.	Risk of burning fuel falling out	No												
AVCP: System(s) of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 3																																				
7.	<table border="1"> <tr> <td>Notified Body:</td> <td>ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK</td> </tr> <tr> <td>Test Report no:</td> <td>N°2013/0020</td> </tr> </table>	Notified Body:	ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK	Test Report no:	N°2013/0020																																
Notified Body:	ARGB NB 2013 Rodestraat 125 B-1630 LINKEBEEK																																				
Test Report no:	N°2013/0020																																				
8.	<table border="1"> <tr> <td>Declared performance:</td> <td></td> </tr> <tr> <td>Harmonized technical specification</td> <td>EN13229:2001/A2:2004/AC:2007</td> </tr> <tr> <td>Essential characteristics</td> <td>Performance</td> </tr> <tr> <td>Fire safety</td> <td></td> </tr> <tr> <td>Reaction to fire</td> <td>A1</td> </tr> <tr> <td>Distance to combustible materials</td> <td>Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.</td> </tr> <tr> <td>Risk of burning fuel falling out</td> <td>No</td> </tr> </table>	Declared performance:		Harmonized technical specification	EN13229:2001/A2:2004/AC:2007	Essential characteristics	Performance	Fire safety		Reaction to fire	A1	Distance to combustible materials	Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.	Risk of burning fuel falling out	No																						
Declared performance:																																					
Harmonized technical specification	EN13229:2001/A2:2004/AC:2007																																				
Essential characteristics	Performance																																				
Fire safety																																					
Reaction to fire	A1																																				
Distance to combustible materials	Minimum distances, in mm Front = 800 Top = 800 Floor = 0 Inset installed in a surround insulated according to local recommendation and manufacturer's requirements.																																				
Risk of burning fuel falling out	No																																				

Emission of combustion products	CO [0.18%] PM [80mg/m3]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T[173°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	16.9 kW
Room heating output	-kW
Water heating output	-*kW
Energy efficiency	η [79%]

DECLARATION:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer by:

Alain Castagnol

Président TOTEM FIRE S.A.S

(Name and function)

Malissard 2017/07/18

(Place and date issue)

(Signature)